



MS20756 FLANGE

4-hole sizes thru -32. 6-hole sizes thru -40 and -48.

Eaton's Aeroquip® Hose and Flanged Fittings Recommended Operating Pressures

Experience with MS20756 (formerly AN756) type flanges in higher pressure applications indicates that a reduced proof pressure should be used in the larger sizes. The chart below lists the recommended maximum proof pressures for various Aeroquip hose styles with this type flange fitting. In addition, when jump size fittings are used, the proof pressure shall be limited to the flange or hose proof pressures, whichever is lowest. This

limitation is necessitated by reported warping of the flange and shoulder, with subsequent failure of the gasket seal, when subjected to the usual minimum 2X operating proof pressures for certain hose styles.

MS20756 flanged fittings shall be installed in accordance with MS33786 (supersedes AND10086) using an AN763 gasket. Maximum operating temperature for this type of flange is limited to +275°F (+135°C) by MS20756.

**Recommended
Pressures for Aeroquip
Hose and Fittings Used
with MS20756 Type
Flanged Fittings**

Specifications

Hose Part Number	Swivel Nut Fittings		MS20756 Type Flange Fittings	
	Max. Operating Pressure psi (bar)	Min. Proof Pressure psi (bar)	Max. Operating Pressure psi (bar)	Max. Proof Pressure psi (bar)
302A-16	800 (55.15)	1600 (110.31)	800 (55.15)	1250 (86.18)
302A-20	600 (41.36)	1250 (86.18)	500 (34.47)	750 (51.71)
302A-24	500 (34.47)	1000 (68.94)	500 (34.47)	750 (51.71)
302A-32	350 (24.13)	700 (48.26)	350 (24.13)	700 (48.26)
302A-40	250 (17.23)	500 (34.47)	250 (17.23)	500 (34.47)
303-12	1500 (103.42)	3000 (206.84)	1250 (86.18)	1500 (103.42)
601-12	1000 (68.94)	2000 (137.89)	1000 (68.94)	1500 (103.42)
601-16	750 (51.71)	1500 (103.42)	750 (51.71)	1250 (86.18)
601-20	500 (34.47)	1300 (89.63)	500 (34.47)	750 (51.71)
601-24	250 (17.23)	800 (55.15)	250 (17.23)	750 (51.71)
601-32	200 (13.78)	600 (41.36)	200 (13.78)	600 (41.36)
666-12	1000 (68.94)	2000 (137.89)	1000 (68.94)	1500 (103.42)
667-16	1250 (86.18)	2500 (172.36)	1000 (68.94)	1250 (86.18)
667-20	1000 (68.94)	2000 (137.89)	500 (34.47)	750 (51.71)
667-24	1000 (68.94)	2000 (137.89)	500 (34.47)	750 (51.71)

Eaton
Aerospace Group
Fluid & Electrical Distribution Division
300 South East Avenue
Jackson, Michigan 49203-1972
Phone: (517) 787 8121
Fax: (517) 789 2947



Powering Business Worldwide

Eaton
Aerospace Group
9650 Jeronimo Road
Irvine, California 92618
Phone: (949) 452 9500
Fax: (949) 452 9555
www.eaton.com/aerospace

Copyright © 2013 Eaton
All Rights Reserved
Form No. DS100-31B
(Supersedes ASB-71)
March 2013